

ADDITIONAL SPECIFICATIONS FOR CALIBRATION OF TRANSMITTERS WITH PROCESS CONNECTIONS

Dear customer,

please complete this form and send it back within 3 working days after order by fax using the following number +42 572 411 497. If no additional specification will be made, the transmitter will be calibrated according BD SENSORS standards

| Company: |
|---|
| Order number: Order position: |
| Please fill here Type and ordering number of transmitter: |
| |
| Colibration to magazitures |
| Calibration temperatures |
| Standard (without specification) |
| Ambient temperature 20 °C |
| Option (please mark) |
| O Calibrate by medium temperature °C (± 10°C) valid for following conditions: ► surrounding: ambient temperature 20 °C ► max. calibration temperatures: 200 °C ► compensation range: ± 25 °C ► for vacuum ranges < 250 mbar: max. calibration temperature is 70 °C. ► with vacuum ranges and calibration temperature higher 70 °C please contact sales department |
| Installation position (for pressure ranges up to 4 bar; with higher pressure ranges the installation position is negligible) |
| Standard (without specification) 0° 180° 90° other |
| Other information |
| Working temperature range: fromup to°C |
| Medium in normal operation: |
| Temperature at the cleaning / sterilisation: max °C |
| Medium for the cleaning / sterilisation: |
| Date and signature: BD SENSORS job number |

Tel.: +420 572 411 011 Fax: +420 572 411 497