


## Ordering code DMP 304

31.5.2016

### DMP 304

Pressure transmitter



Pressure									
gauge	2	2	0						
Input [bar]									
0 ... 2000				2	0	0	4		
0 ... 4000				4	0	0	4		
0 ... 5000				5	0	0	4		
0 ... 6000				6	0	0	4		
Output									
4...20 mA / 2-wire									1
0...10 V / 3-wire									3
Intrinsic safety 4...20 mA/2-wire									E
Customer									9
Accuracy									
0,5% (standard)									5
by agreement 0,25%									2
Measured values table for accuracy 0,5% (only on customer request)									N
Customer									9
Electrical connection									
Connector DIN 43650 (ISO 4400) (IP 65)									1 0 0
Connector Binder Serie 723 5-pin (IP 67)									2 0 0
Cable gland / cable length specify (IP 67)									T A 0
+ PVC cable / 1 m									
Cable gland potted / cable length specify (IP 68)									T R 0
+ PVC cable / 1 m									
M 12 x 1 (4-pin) (Binder 713) (IP 67)									M 0 0
MIL-/Bendix (Typ PT 02 A 10-6 P)									B G 0
Customer									9 9 9
Mechanical connection									
9/16-18 UNF internal thread									V 0 0
M16 x 1,5 internal thread									P 0 0
M 20 x 1,5 internal thread									D 2 8
Customer									9 9 9
Special version									
Optional									0 4 1
Customer									9 9 9

0,-...without additional charge

On request (OR)...in accordance with the producer

This data sheet contains product specification; properties are not guaranteed.

Subject to change without notice.



BD SENSORS s.r.o.  
Hradištská 817  
CZ – 687 08 Buchlovice

Tel.: +420 572 411 011  
Fax: +420 572 411 497

www.bdsensors.cz  
info@bdsensors.cz



The company BD SENSORS s.r.o. is certified by TÜV SÜD Czech according to the standard ISO 9001.