

Ordering code DS 6

31.5.2016

DS 6

Pressure switch (0 ... 2 / 400 bar)

Pressure

	1	2	3	4	5	6	7	8	9	0
gauge	6	8	5							
absolute	6	8	6							
Input [bar]										
2				2	0	0	1			
5				5	0	0	1			
10				1	0	0	2			
20				2	0	0	2			
50				5	0	0	2			
100				1	0	0	3			
200				2	0	0	3			
400				4	0	0	3			
Customer				9	9	9	9			
Number of switching output										
without switching output										0
1 switching output										1
2 switching output										2
Analogue output										
Without analogue output										0
Customer										0
Electrical connection										
M 12 x 1 (5-pin)										N 1 0
Customer										9 9 9
Mechanical connection										
G 1/4" DIN 3852								3	0	0
Customer								9	9	9
Seals										
Viton (FKM) (PN < 100 bar)										1
NBR (PN ≥ 100 bar)										5
Customer										9
Setting code										
BD SENSORS setting - standard										0 0 0
Customer										9 9 9
Special version										
Standard										0 0 0
Version for oxygen										0 0 7
Customer										9 9 9

Software for the pressure switch DS 6
P6-DS6-N00-000 - Programming device P6 for DS6
CIS_G - ADAPT 3 + SW P-SET for DS 6 and incl. Cable

0,-...without additional charge
On request...in accordance with the producer
Subject to change without notice.
Attention: a discount for DS 6 - according to agreement. No standard customers discount.
This data sheet contains product specification; properties are not guaranteed.
Subject to change without notice.

This dokument contains product specification; properties are not guaranteed.
Detailed information about options are defined in the datasheet. Subject to change without notice.



BD SENSORS s.r.o.
Hradištská 817
CZ – 687 08 Buchlovice

Tel.: +420 572 411 011
Fax: +420 572 411 497

www.bdsensors.cz
info@bdsensors.cz



The company BD SENSORS s.r.o. is certified by TÜV SÜD Czech according to the standard ISO 9001.