


Ordering code HU 300

3.1.2020

HU 300

Pressure transmitter (0 ... 5000/15000 psi)



	H	U	0								
Input [psi]											
5000	P	5	K	0							
6000	P	6	K	0							
10000	P	1	0	K							
15000	P	1	5	K							
Customer	9	9	9	9							
Output											
4 ... 20 mA / 2 wire										1	
0 ... 5 V / 3 wire										4	
Intrinsic safety Ex ia 4 ... 20 mA / 2 wire										E	
3 mV/V / 4-wire										V3	
Customer										9	
Accuracy											
0,50% (P _N > 10 mbar)										5	
Customer										9	
Electrical connection											
MIL-/ Bendix (6-pin) Type PT02_E10-6P-023										B	2
Glenair (4-pin) GC379-2-14S-2P										B	Z
Cable outlet IP 68 with FEP-cable										T	R
Customer										9	9
Mechanical connection											
WECO 2" 1502										H	U
WECO 2" 2002/2202										H	U
Customer										9	9
Pressure port											
Stainless steel 1.4548 (17-4PH)										7	8
Customer										9	9
Diaphragm											
Stainless steel 1.4548 (17-4PH)										Z	8
Customer										9	9
Special version											
Standard											0
Customer											0
											0
											9
											9
											9

0,... without additional charge
 On request...in accordance with the producer
 Standard EN 837-1/-3 corresponds to original Standard DIN 16288
 Additional charge for calibration and temperature compensation are not subject to reduction.
 This data sheet contains product specification; properties are not guaranteed.
 Subject to change without notice.

This dokument contains product specification; properties are not guaranteed. Detailed information about options are defined in the datasheet. Subject to change without notice.



BD SENSORS s.r.o.
 Hradištská 817
 CZ – 687 08 Buchlovice

Tel.: +420 572 411 011
 Fax: +420 572 411 497

www.bdsensors.cz
 info@bdsensors.cz



The company BD SENSORS s.r.o. is certified by TÜV SÜD Czech according to the standard ISO 9001.