

Ordering code LMP 308i

31.5.2016

LMP 308i

Stainless steel submersible transmitter (0 ... 0,4 bar / 20 bar)

Pressure																						
gauge			4	4	0																	
measured value in m H2O			4	4	1																	
Input	[mH ₂ O]	[bar]																				
	4.0	0.40		4	0	0	0															
	10	1.0		1	0	0	1															
	25	2.5		2	0	0	1															
	40	4		4	0	0	1															
	100	10		1	0	0	2															
	200	20		2	0	0	2															
Customer				9	9	9																
Housing																						
Stainless steel 1.4571								1														
Customer								9														
Diaphragm																						
Stainless steel 1.4435								1														
Customer								9														
Output signal																						
4 ... 20 mA / 2 wire										1												
0 ... 10 V / 3 wire										3												
Intrinsic safety Ex ia 4 ... 20 mA / 2 wire										E												
Intrinsic safety for mines M1 Ex ia 4 ... 20 mA / 2 wire										F												
Customer										9												
Seals																						
Viton (FKM)										1												
EPDM										3												
Customer										9												
Electrical connection																						
Without cable part												0										
PVC - cable (price for 1 m)												1										
PUR - cable (price for 1 m)												2										
FEP - cable with teflon sheath (price cena for 1 m)												3										
TPE - cable for temperature up to 125°C (price for 1m)												4										
Customer												9										
Accuracy																						
0,10% of range															1							
0,10% of range with calibration including certificate															P							
0,10% production set up on selected range without certificate															I							
0,10% production set up on selected range with certificate															H							
Customer															9							
Cable length																						
without cable													0	0	0							
in whole meters, e.g. 3 m													0	0	3							
in whole meters, e.g. 15 m													0	1	5							
Special versions																						
Standard																					1 1 1	
Interface RS 232 (communication port inside the probe)																					1 2 1	
Interface RS 232 (communication via cable, max. length 20m)																					6 3 0	
cable protection with corrugated pipe																					1 2 3	
stainless steel corrugated pipe (price for 1 m)																					0 4 3	
Customer																					9 9 9	
Accessories for submersible transmitter																						
Cable part + price for cabel in whole meters																						5000722
Terminal clamp - zinc plated																						1003440
Terminal clamp - stainless steel 1.4301																						1000278

0,- ... without additional charge
 On request ... in accordance with the producer
 Additional charge for calibration is not subject to reduction
 This data sheet contains product specification; properties are not guaranteed
 Subject to change without notice.

This dokument contains product specification; properties are not guaranteed. Detailed information about options are defined in the datasheet. Subject to change without



BD SENSORS s.r.o.
 Hradištská 817
 CZ – 687 08 Buchlovice

Tel.: +420 572 411 011
 Fax: +420 572 411 497

www.bdsensors.cz
 info@bdsensors.cz



The company BD SENSORS s.r.o. is certified by TÜV SÜD Czech according to the standard ISO 9001.

Information about options are defined in the datasheet. Subject to change without notice.



BD SENSORS s.r.o.
Hradištská 817
CZ – 687 08 Buchlovice

Tel.: +420 572 411 011
Fax: +420 572 411 497

www.bdsensors.cz
info@bdsensors.cz

The company BD SENSORS s.r.o. is certified by TÜV SÜD Czech according to the standard ISO 9001.

