

Ordering code OEM 17.600G

31.5.2016

OEM 17.600G



Pressure transmitter (0 ... 6 / 600 bar)

Pressure [bar]

0 ... 6	6	0	0	1																	
0 ... 10	1	0	0	2																	
0 ... 16	1	6	0	2																	
0 ... 25	2	5	0	2																	
0 ... 40	4	0	0	2																	
0 ... 60	6	0	0	2																	
0 ... 100	1	0	0	3																	
0 ... 160	1	6	0	3																	
0 ... 250	2	5	0	3																	
0 ... 400	4	0	0	3																	
0 ... 600	6	0	0	3																	
Customer	9	9	9	9																	

Input [bar]

Gauge																					R
-------	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	---

Output

4 ... 20 mA / 2 wire																					1
0 ... 10 V / 3 wire																					3
10 ... 90% of Vs / 3-wire ratiometric (Vs = 2,7 ... 5 VDC)																					R
Customer																					9

Accuracy

0,50%																					5
0,5% calibration including certificate																					T
Customer																					N
																					9

Electrical connection

Connector DIN 43650 (ISO 4400) (IP 65)																					1	0	0
Cable gland PG7 / cable length specify (IP 67)																					4	0	0
+ PVC cable / 1 m																							
Plug Micro																					C	1	0
Increase of coverage for IP 67 (for connector DIN 43650) (ISO 4400)																					E	0	0
M 12 x 1 (4-pin) (Binder 713) (IP 67)																					M	0	0
Cable outlet / cable length specify (IP 68)																					T	A	0
+ PVC cable / 1 m																							
Customer																					9	9	9

Mechanical connection

G 1/2" EN 837-1/-3 (manometric)																					2	0	0
G 1/4" DIN 3852 (only with seals "P")																					3	0	0
G 1/4" EN 837-1/-3 (manometric)																					4	0	0
1/4" NPT																					N	4	0
Customer																					9	9	9

Seals

Without - welded + Viton (FKM)																							P
Without - welded																							2
Customer																							9

Special version

Standard																							0	0	0
Oxygen application (not possible with G 1/4 " DIN 3852)																							0	0	7
Oil and grease free																							0	0	8
Customer																							9	9	9

0,-...without additional charge

On request... in accordance with the producer

Standart EN 837-1/-3 corresponds to original Standart DIN 16288

Additional charge for calibration and temperature compensation are not subject to reduction.

This data sheet contains product specification; properties are not guaranteed.

Subject to change without notice



BD SENSORS s.r.o.
Hradištská 817
CZ – 687 08 Buchlovice

Tel.: +420 572 411 011
Fax: +420 572 411 497

www.bdsensors.cz
info@bdsensors.cz



The company BD SENSORS s.r.o. is certified by TÜV SÜD Czech according to the standard ISO 9001.