

Ordering code PA 430

31.5.2016

PA 430

Plug-on display
Version



Standard version									
Analogue output									
4 ... 20 mA / 2 wire	8	5	0						
0 ... 10 V / 3 wire									1
Intrinsic safety Ex ia 4 ... 20 mA / 2 wire									3
Customer									E
Contact									
Without switching output									0
1 PNP - switching output (3-wire output only 5-pin connector)									1
2 PNP - switching output (only 5-pin connector, 200, N00)									2
Electrical connection (input)									
Connector DIN 43650 (ISO 4400) (IP 65)									1 0 0
Connector Binder 723 - 5-pin (IP 65)									2 0 0
Connector M 12 x 1 5-pin metal version (IP 65)									N 1 0
Unit									
Without description									0
bar									1
mbar									2
m H2O									3
Mpa									4
kPa									5
mA									A
°C									C
°C dp									D
Kelvin									K
mm/s									M
%									P
Volt									V
Customer									9
Label on display									
Standard									1
Neutral									N
Customer									9
Special version									
Standard									0 0 0
Customer									9 9 9

0,-...without additional charge

On request...in accordance with the producer

With connector DIN 43650 and output 4...20 mA/2-wire only max. 1 switching output possible;

This dokument contains product specification; properties are not guaranteed. Detailed information about options are defined in the datasheet. Subject to change without notice.



BD SENSORS s.r.o.
Hradištská 817
CZ – 687 08 Buchlovice

Tel.: +420 572 411 011
Fax: +420 572 411 497

www.bdsensors.cz
info@bdsensors.cz

The company BD SENSORS s.r.o. is certified by TÜV SÜD Czech according to the standard ISO 9001.

