

ADDITIONAL SPECIFICA	FIONS FOR CALIBRATION
OF TRANSMITTERS WITH	PROCESS CONNECTIONS

Dear customer,

please complete this form and send it back within 3 working days after order by email <u>sale@bdsensors.cz</u>. If no additional specification will be made, the transmitter will be calibrated according BD SENSORS standards.

Company:
Order number: Order position:
Please fill here Type and ordering number of transmitter:
Calibration temperatures
Standard (without specification)
Ambient temperature 20 °C
Option (please mark)
O Calibrate by medium temperature °C (± 10°C)
valid for following conditions: ► surrounding: ambient temperature 20 °C
 max. calibration temperatures: 200 °C compensation range: ± 25 °C
 for vacuum ranges < 250 mbar: max. calibration temperature is 70 °C. with vacuum ranges and calibration temperature higher 70 °C please contact sales department
Installation position (for pressure ranges up to 4 bar; with higher pressure ranges the installation position is negligible)
Standard Option (please mark)
(without specification)OOO0°180°90°other
Other information
Working temperature range: from up to °C
Medium in normal operation:
Temperature at the cleaning / sterilisation: max °C
Medium for the cleaning / sterilisation:
Date and signature:BD SENSORS job number
BD SENSOKS JOD NUMBER



BD SENSORS s.r.o. Hradišťská 817

CZ - 687 08 Buchlovice info@bdsensors.cz
The company BD SENSORS s.r.o. is certified by Bureau Veritas Czech according to the standard ISO 9001.

Tel.: +420 572 411 011

www.bdsensors.cz