



# LMP 307T

## Level and Temperature Transmitter

Stainless Steel Sensor

accuracy according to IEC 60770:  
0.35 % / 0.5 % FSO

### Nominal pressure

from 0 ... 1 mH<sub>2</sub>O up to 0 ... 250 mH<sub>2</sub>O

from 0 ... 30 °C up to 0 ... 70 °C

others on request

### Output signals

2-wire: 4 ... 20 mA (pressure)

2-wire: 4 ... 20 mA (temperature)

others on request

### Special characteristics

- ▶ diameter 27 mm
- ▶ separate output signals for pressure and temperature ranges
- ▶ integrated Pt 100 thermal element
- ▶ small thermal effect
- ▶ high accuracy
- ▶ easy handling

### Optional versions

- ▶ Drinking water certificate acc. to DVGW and KTW
- ▶ different kinds of cables
- ▶ different kinds of seal materials
- ▶ customer specific versions

BD SENSORS has developed the stainless steel submersible probe LMP 307T for continuous level and temperature measurement in water and in clean to lightly-soiled liquids.

The advantage: simultaneous recording of level and temperature with separate independent signal amplification. The maintenance and wiring costs are considerably reduced.

In addition to classical signal processing of the level, an additional signal circuit independent of the level which converts the temperature signal into a 4 ... 20 mA analogue signal in 2-wire technology is provided.

Typical application areas are, for example, drinking water purification, monitoring of rainwater overflow basins and river courses, in addition to level measurement in containers or tank batteries.

### Preferred areas of use are



Water / filtrated sewage

e.g. drinking water system

water recycling



Fuel / Oil

e.g. tank farm



Input pressure range														
Nominal pressure gauge	[bar]	0.1	0.16	0.25	0.4	0.6	1	1.6	2.5	4	6	10	16	25
Level	[mH <sub>2</sub> O]	1	1.6	2.5	4	6	10	16	25	40	60	100	160	250
Overpressure	[bar]	0.5	1	1	2	5	5	10	10	20	40	40	80	80
Burst pressure ≥	[bar]	1.5	1.5	1.5	3	7.5	7.5	15	15	25	50	50	120	120

Input temperature range				
Temperature measuring range	standard	0 ... 30 °C	0 ... 50 °C	0 ... 70 °C
	others on request <sup>1</sup>			
<sup>1</sup> min. temperature range: 30°C; max. temperature range: 80°C min. temperature: -10°C; max. temperature: 70 °C				

Output signal / Supply	
2-wire (pressure) <sup>2</sup>	4 ... 20 mA / V <sub>S</sub> = 10 ... 30 V <sub>DC</sub>
2-wire (temperature) <sup>2</sup>	4 ... 20 mA / V <sub>S</sub> = 10 ... 30 V <sub>DC</sub>
<sup>2</sup> the circuits are galvanically isolated from each other	

Performance			
Accuracy (pressure) <sup>3</sup>	standard:	nominal pressure < 0.4 bar:	≤ ± 0.5 % FSO
		nominal pressure ≥ 0.4 bar:	≤ ± 0.35 % FSO
	option 1:	nominal pressure ≥ 0,4 bar:	≤ ± 0.25 % FSO
Accuracy (temperature) <sup>4</sup>	≤ ± 1 °C		
Permissible load	R <sub>max</sub> = [(V <sub>S</sub> - V <sub>S</sub> min) / 0.02 A] Ω		
Influence effects	supply:	0.05 % FSO / 10 V	
	load:	0.05 % FSO / kΩ	
Long term stability	≤ ± 0.1 % FSO / year at reference conditions		
Response time	< 10 ms (for output signal 2-wire (pressure))		
<sup>3</sup> accuracy according to IEC 60770 – limit point adjustment (non-linearity, hysteresis, repeatability)			
<sup>4</sup> Pt 100 class B; compensation time up to 1h depending on constant temperature and environmental respectively mass conditions			

Thermal effects (Offset and Span)		
Nominal pressure P <sub>N</sub>	[bar]	< 0.40
		≥ 0.40
Tolerance band	[% FSO]	≤ ± 1
		≤ ± 0.75
in compensated range	[°C]	0 ... 70

Permissible temperatures		
Permissible temperatures	medium:	-10 ... 70 °C
	storage:	-25 ... 70 °C

Electrical protection <sup>5</sup>	
Short-circuit protection	permanent
Reverse polarity protection	no damage, but also no function
Electromagnetic compatibility	emission and immunity according to EN 61326
<sup>5</sup> additional external overvoltage protection unit in terminal box KL 1 or KL 2 with atmospheric pressure reference available on request	

Electrical connection		
Cable with sheath material <sup>6</sup>	PVC (-5 ... 70 °C)	grey
	PUR (-10 ... 70 °C)	black
	FEP <sup>7</sup> (-10 ... 70 °C)	black
	TPE-U (-10 ... 70 °C)	blue (with drinking water certificate)
	others on request	
<sup>6</sup> cable with integrated air tube for atmospheric pressure reference		
<sup>7</sup> do not use freely suspended probes with an FEP cable if effects due to highly charging processes are expected		


Materials (media wetted)	
Housing	stainless steel 1.4404 (316L)
Seals	FKM; EPDM (with drinking water certificate) others on request
Diaphragm	stainless steel 1.4435 (316L)
Protection cap	POM-C

Miscellaneous	
drinking water certificate	According to DVGW W 270 and UBA KTW (With order please indicate if her device must be certificated for drinking water.)
Connecting cables (by factory)	cable capacitance: signal line/shield also signal line/signal line: 160 pF/m cable inductance: signal line/shield also signal line/signal line: 1µH/m
Current consumption	signal output current: max. 25 mA / signal output voltage: max. 7 mA
Weight	approx. 200 g (without cable)
Ingress protection	IP 68
CE-conformity	EMC Directive: 2014/30/EU

### Wiring diagram


2x2-wire-system (current)






### Pin configuration

Electrical connection	cable colours (DIN 47100)
Supply P+	wh (white)
Supply P-	bn (brown)
Supply T+	gy (gray)
Supply T-	pk (pink)
Shield	ye/gn (yellow / green)

### Dimensions (in mm)



Mounting flange with cable gland		
<b>Technical data</b>		
Suitable for	all probes	
Flange material	stainless steel 1.4404 (316L)	
Material of cable gland	standard: brass, nickel plated on request: stainless steel 1.4305 (303); plastic	
Seal insert	material: TPE (ingress protection IP 68)	
Hole pattern	according to DIN 2507	
<b>Version</b>	<b>Size (in mm)</b>	<b>Weight</b>
DN25 / PN40	D = 115, k = 85, b = 18, n = 4, d = 14	1.4 kg
DN50 / PN40	D = 165, k = 125, b = 20, n = 4, d = 18	3.2 kg
DN80 / PN16	D = 200, k = 160, b = 20, n = 8, d = 18	4.8 kg
<b>Ordering type</b>		<b>Ordering code</b>
DN25 / PN40 with cable gland brass, nickel plated		5000275
DN50 / PN40 with cable gland brass, nickel plated		5000278
DN80 / PN16 with cable gland brass, nickel plated		5000279
<b>Terminal clamp</b>		
<b>Technical data</b>		
Suitable for	all probes with cable $\varnothing$ 5.5 ... 10.5 mm	
Material	standard: steel, zinc plated optionally: stainless steel 1.4301 (304)	
Weight	approx. 160 g	
<b>Ordering type</b>	<b>Ordering code</b>	
Terminal clamp, steel, zinc plated	1003440	
Terminal clamp, stainless steel 1.4301 (304)	1000278	
<b>Display program</b>		
<p><b>CIT 200</b> Process display with LED display</p> <p><b>CIT 250</b> Process display with LED display and contacts</p> <p><b>CIT 300</b> Process display with LED display, contacts and analogue output</p> <p><b>CIT 350</b> Process display with LED display, bargraph, contacts and analogue output</p> <p><b>CIT 400</b> Process display with LED display, contacts, analogue output and Ex-approval</p> <p><b>CIT 600</b> Multichannel process display with graphics-capable LC display</p> <p><b>CIT 650</b> Multichannel process display with graphics-capable LC display and datalogger</p> <p><b>CIT 700</b> Multichannel process display with graphics-capable TFT monitor, touchscreen and contacts</p> <p><b>PA 440</b> Field display with 4-digit LC display</p> <p>For further information please contact our sales department or visit our homepage: <a href="http://www.bdsensors.com">http://www.bdsensors.com</a></p>		
		<p>cable gland M16x1.5 with seal insert (for cable-<math>\varnothing</math> 4 ...)</p> 
		
		

This data sheet contains product specification. Properties are not guaranteed. Subject to change without notice.